

JANTZEN AUDIO

SB Acoustics 3-Way Classic (SBA 3WC)

Designed by Troels Gravesen



Click the buttons below to go to:

[Price List](#)

[Complete Design Article](#)

[Contact / Purchase Form](#)

JANTZEN AUDIO

Troels Gravesen's Introduction:

There's no point denying it! I love the concept of a 3-way classic from an 8" bass driver, a 4" midrange and a 1" tweeter.

We can get an awful lot of good sound from a modest investment.

This may be realised from other brands as well, but here we get proper voice coil formers and suspensions ensuring high mechanical Q and on top of this symmetric drive (SD), something we – to my knowledge – do not find from any other manufacturer at this price level.

IMPORTANT!

Please read our sales terms to read about how the DIY kits are delivered and other important information.

Click [HERE](#) to read sales terms

JANTZEN AUDIO

Drivers used in the construction:

2 x SBA SB23NRXS45-8 (Woofers)



2 x SBA SB12MNRX25-4 (Mid-range units)



2 x SBA SB29RDAC-C000-4 (Tweeters)



JANTZEN AUDIO

Crossover component options (levels)

The “Level 1” has the highest grade of components

Level 1 crossover components:

Coils:

Cross Coils (foil inductors)
Air Core Wire Coils



Tweeter capacitors:

Superior Z-Caps



Mid-range capacitors:

Superior Z-Caps



Other positions:

Cross Caps



Resistors:

Superes (wire wound)



JANTZEN AUDIO

Level 2 crossover components:

Coils:

Cross Coils (foil inductors)
Air Core Wire Coils



Tweeter capacitors:

Standard Z-Caps



Mid-range capacitors:

Standard Z-Caps



Other positions:

Cross Caps



Resistors:

Superes (wire wound)



JANTZEN AUDIO

Damping materials included in the DIY kit:

Damping felt



Polyester damping cloth



Accessories included in the DIY kit:

Binding post terminals (2 pairs)



Port tubes



Cables for internal wiring (PFTE/Silver)



Solder tag strips



Casco SuperFix component fastening glue



Screws for driver mounting



JANTZEN AUDIO

For general accessories click the box below



For SoundCare Super Spikes click the box below

