

# JANTZEN AUDIO

## SBA 741

Designed by Troels Gravesen

**Page 1:** Crossover component overview and kit level comparison

**Page 2:** Damping materials and accessories overview

### BASICS

**Speaker type:**

3-way

**Cabinet:**

27 x 36 x 55 cm, WxDxH.

**System sensitivity:**

86-87 dB/2.8V/1 meter.

**Impedance:**

4-8 Ohms.

Minimum 3.6 Ohms at 125 Hz.

**Power requirement:**

20+ watts/channel.

### Level 1 - Crossover component overview:



**Level 1 kit has higher grade tweeter/midrange capacitors compared to level 2**



Wax Coils (Foil-based coils)



Air & iron core wire coils



**Tweeter capacitors:** Alumen Z-Caps (Pure aluminum foil)



**Midrange capacitors:** Silver Z-Caps (Super MKP)



**Bass capacitors:** Standard Z-Caps (MKP)



Superes wire-wound resistors



### Level 2 - Crossover component overview:

Coils, bass capacitors and resistors are identical to level 1



**Tweeter capacitors:** Silver Z-Caps (Super MKP)



**Midrange capacitors:** Silver & Superior Z-Caps



## Damping materials included:

Grey damping felt



White polyester damping cloth



Combed natural wool stuffing



## Accessories included:

Binding post terminals (4 pairs)



Port tubes (bass reflex)




16 AWG PTFE insulated silver infused cables (for internal wiring)



Solder tag strips (28-pin)



CasCo SuperFix glue (for gluing components to boards)



Black anodized woods screws (for driver mounting)

